

Floor mounted - Tech Data

MODEL

Indoor	RAF-35NXA1	RAF-50NXA1
Outdoor	RAC-35NXA1	RAC-50NXA1
Capacity kW		
Nominal Cooling	3.5	5.0
Nominal Heating	4.2	6.0
Capacity (Range) kW		
Cooling	1.1 - 4.2	1.1 - 5.2
Heating	1.1 - 5.2	2.2 - 7.3
Air Flow l/sec		
Hi / Med / Lo / Sleep	167 / 138 / 113 / 92	180 / 147 / 120 / 103
Energy Efficiency		
EER / AEER Cooling	3.80 / 3.74	3.34 / 3.30
COP / ACOP Heating	3.96 / 3.90	3.87 / 3.83
Star Rating Cooling	2.5	2.0
Star Rating Heating	3.0	3.0
Noise Levels (dB(A))		
Indoor Unit		
Hi / Med / Lo / Sleep	42 / 35 / 29 / 25	46 / 37 / 30 / 25
Outdoor Unit		
Cooling / Heating	47 / 49	52 / 52
Sound Power Level	64	67
Dimensions (mm)		
Indoor (W x H x D)	760 x 600 x 235	760 x 600 x 235
Outdoor (W x H x D)	841 x 548 x 335	887 x 600 x 345
Weights (kg)		
Indoor / Outdoor	14 / 36	14 / 40
Operating Range		
Outdoor Op. Temp. (Cooling)	-10°C to 43°C	-10°C to 43°C
Outdoor Op. Temp. (Heating)	-15°C to 24°C	-15°C to 24°C
Refrigerant Type	R410A	R410A
Pipe Sizes (mm)		
Refrig pre charge length	20	20
Min / Max Pipe Length / Lift	3 / 20 / 10	3 / 20 / 10
Power		
Power Supply	230 - 240 Volt / 50 Hz / 1 Phase	230 - 240 Volt / 50 Hz / 1 Phase
Run Amps / Phase (A/ph.)		
Cooling / Heating	4.12-4.5 / 4.61-5.04	6.36-6.93 / 6.99-7.62
Power Supply To Interconnecting Wire	2 Core + E	2 Core + E

Rated capacity measured in accordance with AS/NZS 3823 conditions: Cooling: Indoor 27°C db / 19°C wb; Ambient 35°C db
Heating: Indoor 20°C db; Ambient 7°C db / 6°C wb
Mains power source - AC 230V and 50Hz

3.5 - 5.0kW

RAF/RAC-35NXA1
RAF/RAC-50NXA1



**Standard
Wireless
Controller***
(RAR-3U1)



Outdoor unit
(RAC-35NXA1)



Australia
5 YEAR WARRANTY

New Zealand
6 YEAR WARRANTY

* Controllers and some control features differ from those featured in this brochure.